














TECHNICAL SPECIFICATIONS



Type		Length mm	Width mm	Truck pay-load in tonnes	Approx. capacity in kg	Approx. capacity in m ³	Weight of the basic machine in kg	Length in mm	Width in mm	Height in mm	Approx. fuel consumption kg/h
ATC 25M		1,900	1,600	2.0	1,250	0.8	780	2,430	1,600	920	0.5
ATC 25	 Standard model	1,900	1,600	3.0-4.0	3,000	1.7	950	2,570	1,500	1,420	0.8
ATC 50	 Standard model	3,150	2,140	6.7	5,000	3.0	1,600	3,600	2,000	1,540	2.0
ATC 50S		3,150	2,140	7.7	6,000	3.6	1,700	3,600	2,000	1,740	2.0
ATC 50/2K		3,150	2,140	6.9	5,000	3.0	1,950	3,600	2,000	1,540	2.0
ATC 60	 Standard model	3,650	2,140	7.7	6,000	3.6	1,800	4,100	2,000	1,540	2.5
ATC 75	 Standard model	4,150	2,140	9.5	7,500	4.6	2,000	4,600	2,000	1,540	3.0
ATC 75S		4,150	2,140	11.0	9,000	5.4	2,200	4,600	2,000	1,740	3.0
ATC 75/2K		4,150	2,140	9.7	7,500	4.5	2,600	4,600	2,000	1,540	3.0
ATC 100	 Standard model	5,150 or 4,870	2,140	12.5	10,000	6.0	2,500	5,600	2,000	1,540	4.0
ATC 100S		5,150 or 4,870	2,140	18.0	15,000	8.4	2,800	5,600	2,000	2,040	4.0
ATC 100/2K		5,150 or 4,870	2,140	12.7	10,000	6.0	2,850	5,600	2,000	1,540	4.0
ATC 100S Jumbo		5,650	2,400	24.0	20,000	12.0	4,000	6,550	2,400	2,070	5.0

All containers are approved, are subjected to a TÜH (Technical Inspectorate of Hessen) acceptance inspection and bear the GS mark (tested safety).



We reserve the right to make technical changes.